

Appl. No. 10/691,104
Reply to Office Action of April 6, 2005

Best Available Copy

IN THE CLAIMS

1. (Currently Amended) A method of learning associations between a plurality of tires each having a unique identification code and a plurality of locations for tires,
comprising: the method comprising the steps of;
initiating a timer before receiving a first identification code;
receiving the unique identification codes from each tire of the plurality of tires in response to a change in tire pressure in said each tire in a predetermined order of the plurality of locations for tires; [[and]]
resetting said timer after receiving each identification code;
correlating the receipt of the unique identification codes to the predetermined order of the plurality of locations for tires to thereby associate each tire of the plurality of tires to one location of the plurality of locations for tires; and
terminating said method if said timer indicates that a predetermined threshold of time has expired before an identification code is received.
2. (Original) The method of claim 1, wherein the change in tire pressure is an operator-supplied change in tire pressure.
3. (Original) The method of claim 1, the method further comprising the steps of:
determining if a particular received unique identification code is a first unique identification code received; and
if so, erasing existing correlated unique identification codes.
4. (Cancelled)

Appl. No. 10/691,104
Reply to Office Action of April 6, 2005

5. (Currently Amended) ~~The method of claim 1, further comprising the steps of:~~
A method of learning associations between a plurality of tires each having a unique identification code and a plurality of locations for tires, the method comprising:
receiving the unique identification codes from each tire of the plurality of tires in response to a change in tire pressure in said each tire in a predetermined order of the plurality of locations for tires;
correlating the receipt of the unique identification codes to the predetermined order of the plurality of locations for tires to thereby associate each tire of the plurality of tires to one location of the plurality of locations for tires;
testing each second and subsequently received identification code to determine if said identification code is unique compared to said identification codes already stored; and
storing only identification codes that are determined to be unique compared to said identification codes already stored.
6. (Original) The method of claim 1, wherein said receiving step further comprises the step of communicating receipt of said unique identification code to a user.

Appl. No. 10/691,104
Reply to Office Action of April 6, 2005

7. (Currently Amended) A tire pressure monitor system for a vehicle having a plurality of tires each mounted on a wheel at one of a plurality of locations relating to said vehicle, the tire pressure monitor system comprising:

a plurality of tire pressure detectors each coupled to one of the plurality of wheels, each tire pressure detector further comprising:

a transmitter having a unique identification code; and

a pressure sensor configured to detect changes in the pressure in said one tire mounted on said wheel;

a receiver configured to receive said transmitted unique identification codes;

a first processor coupled to said receiver, wherein said processor is configured to respond to a user-supplied command to relearn associations between said identification codes and said locations by accepting said received identification codes in a predetermined order related to said locations; and

a memory coupled to said first processor, wherein said memory is configured to store each said identification code in association with each said respective location, wherein each said detector processor is configured to:

determine a magnitude of the pressure change within a predetermined time period;

compare the pressure change magnitude within the predetermined time period to a predetermined threshold;

control the transmitter to transmit pressure data and the identification code periodically if the determined magnitude is less than the predetermined threshold; and

control the transmitter to transmit at least the identification code immediately if the determined magnitude is greater than the predetermined threshold.

8. (Currently Amended) The tire pressure monitor system of claim [[1]] 7, wherein each tire pressure detector further comprises a detector processor coupled to said transmitter and to said pressure sensor and configured to control said transmitter to transmit said unique identification code in response to a user-supplied signal.

Appl. No. 10/691,104
Reply to Office Action of April 6, 2005

9. (Currently Amended) The tire pressure monitor system of claim [[1]] 8, wherein said user-supplied signal comprises a pressure change in said each tire, and wherein said pressure sensor is configured to provide an indication of the pressure change to said detector processor.

10. (Cancelled)

11. (Currently Amended) The tire pressure monitor system of claim [[1]] 7, further comprising:

at least one device for communicating with a human user, said at least one device coupled to and controlled by said first processor.

12. (Currently Amended) The tire pressure monitor system of claim [[1]] 11, wherein said at least one device for communicating generates an indication that said unique identification code has been stored.

13. (Currently Amended) The tire pressure monitor system of claim [[1]] 11, wherein said at least one device generates an indication that said first processor has been commanded to relearn said associations.

14. (Currently Amended) The tire pressure monitor system of claim [[1]] 7, wherein said transmitter comprises a plurality of transmitters each being coupled to each tire ~~comprises a transmitter coupled to a valve stem of one of said tires each said tire.~~

15. (Currently Amended) The tire pressure monitor system of claim [[1]] 14, wherein said plurality of transmitters is equal to said plurality of tires.

16. (Currently Amended) The tire pressure monitor system of claim [[1]] 7, wherein said vehicle has four wheels and said predetermined order consists of the sequence: left front, right front, right rear, left rear.

Appl. No. 10/691,104

Reply to Office Action of April 6, 2005

17. (Currently Amended) An apparatus, comprising:
an electronic automotive tire pressure monitor receiver configured to relearn associations between tire pressure transmitter identification codes and locations for vehicle tires based at least partially upon a user-supplied tire pressure change to each tire in a predetermined order.
18. (Currently Amended) The apparatus ~~electronic automotive tire pressure monitor~~ of claim [[1]] 17, further configured to signal a user with pre-existing devices in the vehicle.
19. (Cancelled)
20. (Cancelled)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.